



Model 6500

FRICION FLOW LOOP

The Model 6500 Friction Flow Loop fully automated system includes hardware and software to measure the friction pressure of fluids. It determines the associated affects friction reducers have on fluids over a wide range of pressures and flow rate conditions and through different pipe diameters.

This Model circulates fluid through two test sections of various diameters in order to generate differential pressure versus flow rate data. This data helps to determine the effectiveness and longevity of various friction reducing agents added to the test fluids.

The system incorporates a low shear, progressive cavity pump for injection of base fluids with the flow rate controlled by a Coriolis flow meter. Differential pressure transducers are provided on each tubing diameter for multiple data readings per test. Fluid can be injected into the flow stream via an optional metering pump or added directly into a 15 gallon reservoir mixing tank.

The software is designed to be easy to use and powerful enough to calculate and collect all required data during the test cycle. The software allows the operator total control over flow rate, test time, temperature (optional) of each individual test. All data and test parameters are stored in a test-specific .CSV file for analysis.



FEATURES

- ✓ Open or Closed Loop Architecture
- ✓ Easy to Set-Up, Operate, Clean, Maintain and Calibrate
 - Flush-and-Fill automation for easy system cleanup
- ✓ Wall or Floor Mountable
- ✓ ½" and ¾" O.D., 25' length tubing sections (10' test sections)
- ✓ Coriolis Mass Flow Meter
 - Accurate measurement and feedback of flow rate
- ✓ Over Pressure Relief Valves
 - Safety control prevents operation above the designed pressures
- ✓ Progressive Cavity Style Pump
 - Provides very low shear to fluids during injection
- ✓ Real Time Display of Reynolds Number, Flow Rate, Temperature, Differential Pressure

Model 6500

Standard Models:

6500-AM-150 150 PSI, Ambient Fluid Temperature

6500-CH-150 150 PSI, With Chiller, Fluid Temperature to 40°F

6500-AM-250 250 PSI, Ambient Fluid Temperature

6500-CH-250 250 PSI, With Chiller, Fluid Temperature to 40°F

Specifications:

Maximum Pressure: 150 PSI (250 PSI Optional)

Flow Rate Range: 2 – 15 Gallons / Minute

Fluid Temperature Range: 60 – 90°F (40°F with Optional Chiller)

Differential Pressure Range (1): 0 – 30 PSI

Differential Pressure Range (2): 0 – 100 PSI

Differential Pressure Accuracy: 0.1% of Full Range

Utilities:

Power Requirements: 208 - 240 VAC, 50 or 60 Hz, 40A


Dimensions (w x d x h): 30' x 4' x 6'

Compressed Air: 80-120 psi

Water: 20-30 psi (for system cleanup)

*Manufacturer's specifications subject to change without notice

Scan the below QR Code with your phone to view product information on our Website.



FOLLOW US ON:



AMETEK®
CHANDLER ENGINEERING

2001 North Indianwood Avenue, Broken Arrow, OK 74012
Tel: +1 918-250-7200 • Fax: +1 918-459-0165
e-mail: chandler.sales@ametek.com • www.chandlereng.com

Houston Sales and Services

4903 W. Sam Houston Parkway, N., Suite A-400, Houston, TX 77041
Tel: +1 713-466-4900 • Fax: +1 713-849-1924