



CHANDLER ENGINEERING

Model 5265 MGSA

MECHANICAL GEL STRENGTH APPARATUS

A Critical Tool for Oil Well Drilling and Cementing

The Model 5265 MGSA Gel Strength Analyzer is an addition to Chandler Engineering's world leading line of cement testing equipment. The need to measure gel development, gel duration and gel strength are critical in the design of cement slurries. The Model 5265 MGSA measures the onset of gel strength as well as the continued development of gel strength. This data equips the operator with the knowledge required to optimize slurry designs and meet critical requirements of well placement.

The Model 5265 MGSA utilizes a precision motor and paddle coupled to a reaction force transducer to measure the phase change. The instrument is designed to condition the slurry at 150 RPM and set the measurement of gel strength at 0.2 degrees per minute. As an added function, the motor can be run at an intermittent motor rate. The geometry of the paddle is industry specific or may be adapted to other geometries as needed. The instrument comes complete with the Quizix Precision Pump System for stable and accurate pressure control. Precision pressure control is critical for the accuracy of gel strength measurement and maintaining gel structure.

FEATURES

- ✓ 0.2 degrees/min or start/stop measurement motor speeds
- ✓ Slurry conditioning at 150 RPM
- ✓ Reaction torque measurement from 10 lbf/100ft² up to 1500 lbf/100ft²
- ✓ Operating temperature up to 450°F (232°C)
- ✓ Operating Pressure up to 20,000 psi (138 MPa)
- ✓ Utilizes Chandler Engineering Model 5270 Data Acquisition and Control Software
- ✓ Quizix Precision Pump System Included



Model 5265MGSA System with Quizix Pump

Model 5265 MGSA

Specifications

Maximum Temperature: 450°F / 232°C

Maximum Pressure: 20000 psi / 138 MPa

Utilities:

Instrument Power: 230 VAC, ±10%, 50/60 Hz, 1 phase

Water: 20-80 psi / 140-550 kPa

Clean dry compressed air: 50-100 psi / 340-690 kPa

Coolant: Water or Ethylene Glycol Solution

Drain: Suitable for hot water

Environmental: Indoor use, altitude up to 6562 ft / 2000 m

Ambient temperature: 60-122°F / 16-50°C

Measurement Specifications:

Accuracy: ±1% of F.S. or better

Paddle speed range: 0.2 degrees/min - 150 RPM

Pressure control accuracy: ±25 psi of F.S.

Regulatory:

Designed to meet ASME, CE/PED and NRTL Certifications

API RP10B-6 Compliant

FOLLOW US ON:



CHANDLER ENGINEERING

2001 North Indianwood Avenue, Broken Arrow, OK 74012

Tel: +1 918-250-7200 • Fax: +1 918-459-0165

e-mail: chandler.sales@ametek.com • www.chandlereng.com

Houston Sales and Services

4903 W. Sam Houston Parkway, N., Suite A-400, Houston, TX 77041

Tel: +1 713-466-4900 • Fax: +1 713-849-1924